

# IN-WELL TECHNOLOGIES INC.

## PVC IN-THE-WELL PRESSURE TANK

- ALL PVC OUTER SHELL
  - END CAPS ARE PERMANENTLY ATTACHED BY A UNIQUE BARB AND GROOVE METHOD
  - CORROSION PROOF CONSTRUCTION
  - LOAD HOLDING CAPACITY 2,000 LBS.
  - MAXIMUM WORKING PRESSURE 100 PSI
  - BUTYL AIR CELL FOR EXCELLENT AIR RETENTION
  - WATER PASSES THROUGH TANK FOR COMPLETE WATER CHANGE
  - DESIGNED FOR A CONSTANT PRESSURE SYSTEM: EITHER VFD OR REGULATING VALVE APPLICATIONS
  - RESIDENTIAL, FARM AND LIGHT INDUSTRY
- 
- FOR 4" AND LARGER WELLS
  - TANK VOLUME UP TO 4.35 GALLONS
  - LARGER PUMP SYSTEMS MAY REQUIRE MULTIPLE TANKS
  - DRAWDOWN VOLUME TO 1.5 GALLONS
  - ALL MATERIAL FDA APPROVED
  - MAXIMUM WORKING TEMPERATURE: 74 DEGREES
  - 5 YEAR WARRANTY FROM DATE OF MANUFACTURE
  - MADE IN THE USA



Model	Tank Volume	System Connectors	Dimensions		Shipping Weight	Load Capacity	Maximum Pressure
			Dia	Length			
PL 35	3.55 Gallons	1 1/4" FNPT	3 1/2"	116"	22 lbs.	2,000 lbs.	100 psi
PL 45	4.35 Gallons	1 1/4" FNPT	4 1/2"	80"	24 lbs.	2,000 lbs.	100 psi

**IN-WELL**  
TECHNOLOGIES INC.

7391 SOUTH PORCUPINE LAKE RD.  
LENA, WI 54139

TOLL FREE: 866-560-2867 • FAX: 920-829-5535  
www.inwelltech.com • EMAIL: info@inwelltech.com