

IN-WELL TECHNOLOGIES INC.

PVC IN-THE-WELL PRESSURE TANK

- ALL PVC OUTER SHELL
 - END CAPS ARE PERMANENTLY ATTACHED BY A UNIQUE BARB AND GROOVE METHOD
 - CORROSION PROOF CONSTRUCTION
 - LOAD HOLDING CAPACITY 2,000 LBS.
 - MAXIMUM WORKING PRESSURE 100 PSI
 - BUTYL AIR CELL FOR EXCELLENT AIR RETENTION
 - WATER PASSES THROUGH TANK FOR COMPLETE WATER CHANGE
 - DESIGNED FOR A CONSTANT PRESSURE SYSTEM: EITHER VFD OR REGULATING VALVE APPLICATIONS
 - RESIDENTIAL, FARM AND LIGHT INDUSTRY
-
- FOR 4" AND LARGER WELLS
 - TANK VOLUME UP TO 4.35 GALLONS
 - LARGER PUMP SYSTEMS MAY REQUIRE MULTIPLE TANKS
 - DRAWDOWN VOLUME TO 1.5 GALLONS
 - ALL MATERIAL FDA APPROVED
 - MAXIMUM WORKING TEMPERATURE: 74 DEGREES
 - 5 YEAR WARRANTY FROM DATE OF MANUFACTURE
 - MADE IN THE USA



| Model | Tank Volume | System Connectors | Dimensions | | Shipping Weight | Load Capacity | Maximum Pressure |
|-------|--------------|-------------------|------------|--------|-----------------|---------------|------------------|
| | | | Dia | Length | | | |
| PL 35 | 3.55 Gallons | 1 1/4" FNPT | 3 1/2" | 116" | 22 lbs. | 2,000 lbs. | 100 psi |
| PL 45 | 4.35 Gallons | 1 1/4" FNPT | 4 1/2" | 80" | 24 lbs. | 2,000 lbs. | 100 psi |

IN-WELL
TECHNOLOGIES INC.

7391 SOUTH PORCUPINE LAKE RD.
LENA, WI 54139

TOLL FREE: 866-560-2867 • FAX: 920-829-5535
www.inwelltech.com • EMAIL: info@inwelltech.com